


NEW ARRIVAL SS-27 	Comparison details	SS-28
R32	Refrigerant	R410A
675	GWP (Global Warming Potential)	2090
2.7 Kw	Cooling capacity	2.8 Kw
9212 BTU	BTU	9554 BTU
Maximum -12°C from ambient temp.	Temperature (cool air)	Maximum -16°C from ambient temp.
0.8 Kw	Power consumption	1.01 Kw
18A / 3.7A	Starting / Running current	20A / 4.6A
5.6m³/min	Cool air volume	4.8m³/min(High) / 4.5m³/min(Low)
9.3m³/min	Hot air volume	11.3m³/min(High) 10.7m³/min(Low)
W400 X D390 X H830	Dimension (mm)	W390 X D430 X H860
32 Kg	Net weight	42 Kg
4L	Drain tank capacity	5L
	Shapes	
 สวิตช์ เลือกโหมดพัดลม (Fan), เย็น (Cool)	Controller	 ปุ่มเปิด - ปิด สามารถเปิดปิดได้ทั้งหน่วย "COOL" "FAN" and "STOP" ปุ่มควบคุมการตั้งค่าโหมดพัดลม สามารถเลือกโหมดพัดลมได้ เป็น 3 โหมด (Fan, Cool, Stop) (ไม่มีในรุ่น SS-406G-36T II) ปุ่มควบคุมการตั้งค่าโหมดพัดลม สามารถเลือกโหมดพัดลมได้ เป็น 3 โหมด (Fan, Cool, Stop) (ไม่มีในรุ่น SS-406G-36T II)